

**TYPE APPROVAL CERTIFICATE****This is to certify:****That the Data transmission cables and systems**with type designation(s)  
**AICI, AIOI, AICU, AIOU**

Issued to

**Cavicel S.p.A.**  
**Pioltello MI, Italy**is found to comply with  
**DNV GL rules for classification – Ships, offshore units, and high speed and light craft****Application :****Fiber optic cable.****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**Issued at **Høvik** on **2017-10-06**for **DNV GL**This Certificate is valid until **2022-10-05**.DNV GL local station: **Milan**Approval Engineer: **Ivar Bull**

---

**Andreas Kristoffersen**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-021091-3**  
 Certificate No: **TAE00000TZ**  
 Revision No: **1**

## Product description

NEK TS606 type: Type AICI (steel wire braid) Outer sheath: SHF1  
 Type AIOI (copper wire braid). Outer sheath: SHF1  
 Type AICU (steel wire braid) or AIOU (copper wire braid). Outer sheath: SHF2 or SHF2 MUD

### Optical fibres

| TYPE OF FIBRES               |                      |                | Single Mode<br>9/125 | Multimode<br>62.5/125 | Multimode<br>50/125 |
|------------------------------|----------------------|----------------|----------------------|-----------------------|---------------------|
| Fibre Code (000)             |                      |                | 009                  | 062                   | 050                 |
| ITU-T type                   |                      |                | G.652B/D             | -                     | G.651               |
| Mode Field<br>Diameter (MFD) | at 1310 nm           | µm             | 9.2 ± 0.4            | -                     | -                   |
|                              | at 1550 nm           | µm             | 10.3 ± 0.5           | -                     | -                   |
| Core Diameter                |                      | µm             | -                    | 62.5 ± 2.5            | 50 ± 2.5            |
| Cladding Diameter            |                      | µm             | 125.0 ± 1.0          | 125.0 ± 1.0           | 125.0 ± 1.0         |
| Coating Diameter             |                      | µm             | 242 ± 7.0            | 242 ± 7.0             | 242 ± 7.0           |
| Numerical Aperture           |                      |                | 0.14                 | 0.275 ±<br>0.015      | 0.200 ±<br>0.015    |
| Attenuation                  | at 850 nm            | dB/km<br>(max) | -                    | ≤ 3.5                 | ≤ 2.8               |
|                              | at 1300 nm           | dB/km<br>(max) | -                    | ≤ 1.0                 | ≤ 1.0               |
|                              | at 1310 nm           | dB/km<br>(max) | ≤ 0.40               | -                     | -                   |
|                              | at 1550 nm           | dB/km<br>(max) | ≤ 0.22               | -                     | -                   |
|                              | at 1625 nm           | dB/km<br>(max) | -                    | -                     | -                   |
| Bandwidth                    | at 850 nm            | MHz x km       | -                    | 160 to > 300          | 400 to ><br>1000    |
|                              | at 1300 nm           | MHz x km       | -                    | 500 to ><br>1000      | 400 to ><br>1500    |
| Chromatic<br>Dispersion      | at 1285 ÷ 1330<br>nm | ps/nm x<br>km  | ≤ 3.0                | -                     | -                   |
|                              | at 1550 nm           | ps/nm x<br>km  | ≤ 18                 | -                     | -                   |
|                              | at 1530 ÷ 1565<br>nm | ps/nm x<br>km  | -                    | -                     | -                   |
|                              | at 1565 ÷ 1625<br>nm | ps/nm x<br>km  | -                    | -                     | -                   |

Other fiber type and qualities are available on request.

Minimum bending diameter of cable( Static ) : 10 x outer diameter  
 Minimum bending diameter of cable( Dynamic ) : 20 x outer diameter

## Application/Limitation

Temperature window

Operation: -40°C to +70°C  
 Installation: -10°C to +70°C

Job Id: **262.1-021091-3**  
 Certificate No: **TAE00000TZ**  
 Revision No: **1**

Storage: -40°C to +70°C

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

## Type Approval documentation

Datasheets: [ST/0203/03](#)

### Test reports:

[22229/08](#), [22240/08](#), [22231/08](#), [22233/08](#), [22235/08](#), [22237/08](#), [22254/08](#),  
[22239/08](#), [22259/08](#), [22256/08](#), [22258/08](#), [22250/08](#), [22261/08](#), [3797/08](#),  
[48SI00005-1](#), [3708/08](#) and [3709/08](#).

IMQ test report CN15S0447511-01 dated 2015/07/14. Test for Oil based drilling fluid EDC 95/11

IMQ test report CN15S0523325-01/1 dated 2015/10/08. Test for IRM902 and IRM903.

IMQ test report CN15S0523325-01/2 dated 2015/11/13. Test for CALCIUM BROMIDE BRINE.

## Tests carried out

|                |            |   |   |
|----------------|------------|---|---|
| DNVGL CP-0402  | 2016-02    | Class program for Optical fiber cables  |   |
| IEC 60794-1-1  | 2015-11    | Optical fibre cables – Part 1-1: Generic specification – General  |   |
| IEC 60794-1-2  | 2013-09    | Optical fibre cables - Part 1-2: Generic specification - Cross reference table for optical cable test procedures  |   |
| IEC 60092-360  | 2014-04    | Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.  |   |
| IEC 60332-3-24 | 2009-02    | Tests on electric and optical fibre cables under fire conditions – Part 3-24: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category C   | Charred portion of sample does not exceed 2,5m above bottom edge of burner. |
| IEC 60754-1    | 2011-11    | Test on gases evolved during combustion of materials from cables – Determination of the amount of halogen acid gas  | Low Halogen:<br><0,5% Halogen   |
| IEC 60754-2    | 2011-11    | Test on gases evolved during combustion of materials from cables – Determination of the degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity | Halogen free:<br>pH > 4,3<br>Conductivity < 10µS                            |
| IEC 61034-1/2  | 2013-07/09 | Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements  | Low smoke   |

Job Id: **262.1-021091-3**  
Certificate No: **TAE00000TZ**  
Revision No: **1**

|               |         |  |   |
|---------------|---------|--|---|
| NEK 606 Ed. 4 | 2009-05 | Cables for offshore installations. Halogen-free and/or mud resistant. Technical specification. | Mud resistance test:<br>IRM903 100°C 7d.<br>Calcium Bromide 70°C 56d.<br><u>Oil based mud:</u><br>Carbo Sea 70°C 56d or<br>EDC 95/11 70°C 56d |
|---------------|---------|--|---|

### Marking of product

CAVICEL - AICI or AIOI - FIBER OPTIC CABLE - MTI-000-\*\*-M1-A1 YR\*\*\*\* - Batch No.-Meter marking  
CAVICEL - AICU or AIOU - FIBER OPTIC CABLE - MTI-000-\*\*-M1-A1 YR\*\*\*\* - Batch No. .-Meter marking

000 = Type of fibres  
\*\* = n° of fibres

### Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE