

Firecel SR 109

**FLEXIBLE/SILICONE INSULATION
OVERALL SCREEN**



F-SR/OS/LSZH 450/750 V

Applications

FIRECEL SR 109 are designed, manufactured and tested for general application in power and signal wiring, for emergency circuit and fire circuit control where high rejection of electrostatic noise is needed.

Operating temperature

40°C to +90°C

Minimum bending radius

8 times the outer diameter.

Cable construction

Conductors

Plain copper conductor flexible according to EN 60228 class 5.

Insulation

High performance fire resistant silicone rubber.

Cabling

Insulated cores are cabled together.

Overall screen

Aluminium/polyester tape with tinned copper drain wire 0,5 mm².

Outer sheath

LSZH thermoplastic compound.

Colour red (other colours on request).

Colour code

Without earth conductor

2 cores: ● ●

3 cores: ● ● ●

4 cores: ● ● ● ●

7 cores and **above**: ● numbered

With earth conductor

3 cores: ● ● ●/●

4 cores: ● ● ● ●/●

5 cores: ● ● ● ● ●/●

7 cores and **above**: ● numbered ●/●

Applicable Standards

Fire resistant

CEI 20-36/2-1
EN 50200 PH60
IEC 60331-21

Flame retardant

EN 60332-1-2 / IEC 60332-1-2

Fire retardant

EN 60332-3-24 (cat.C)
IEC 60332-3-24 (cat.C)

Acid gas emission

EN 60754-1 / IEC 60754-1
EN 60754-2 / IEC 60754-2

Smoke density

EN 61034-2 / IEC 61034-2

N° of cores x size (mm ²)	Outer diameter (mm)	Weight (kg/km)
0.75 mm² flexible		
F-SR/OS/LSZH		
2x0.75	7.6	69
3x0.75	8.0	84
4x0.75	8.7	103
1 mm² flexible		
F-SR/OS/LSZH		
2x1	8.0	78
3x1	8.2	86
4x1	8.9	110
7x1	10.8	176
12x1	13.9	275
19x1	16.4	408
1,5 mm² flexible		
F-SR/OS/LSZH		
2x1.5	8.3	88
3x1.5	8.8	112
4x1.5	9.8	141
7x1.5	11.7	W218
12x1.5	15.3	352
19x1.5	18.2	535
2.5 mm² flexible		
F-SR/OS/LSZH		
2x2.5	9.8	123
3x2.5	10.4	159
4x2.5	11.4	196
7x2.5	13.4	305
12x2.5	17.9	505
19x2.5	21.1	760

Approximate values