




Conducting Value

## DRUMS

DIMENSIONS AND WEIGHT											
DRUMS		06	07	08	09	10	12	14	16	18	20
D	Diameter (mm)	650	750	840	940	1030	1280	1460	1660	1860	2060
L	Width (mm)	450	500	600	550	660	730	850	1010	1350	1400
	Staved Drum Weight (kg)	22	25	37	41	55	81	130	210	325	390
	Shipping Volume (m <sup>3</sup> )	0,19	0,28	0,42	0,48	0,70	1,19	1,81	2,78	4,67	5,94



Drums are manufactured from timber in accordance with the International Plant Protection Convention (IPPC), adopted by the FAO (ISPM 15).

MAX LENGTH (m) PER DRUM TYPE											
DRUMS		06	07	08	09	10	12	14	16	18	20
Cable diameter (mm)											
4		3830									
6		1700	2770	3960	5000						
8		930	1560	2240	2820	4340					
10		580	960	1440	1780	2800	4900				
12		420	660	970	1250	1950	3530	5340			
14		290	460	720	950	1410	2650	3860			
16		190	370	520	710	1070	1950	2890	4170		
18		150	250	420	530	800	1550	2310	3330	4550	
20		110	200	330	420	660	1190	1830	2650	3850	4570
22		100	180	260	330	530	990	1460	2040	2980	3820
24			130	200	260	430	760	1260	1740	2530	3050
26			100	160	210	340	630	1020	1460	2170	2630
28				150	200	280	580	860	1250	1830	2240
30				110	150	250	490	740	1060	1520	1880
32				100	140	200	390	610	880	1280	1600
34					110	180	370	580	810	1170	1470
36					100	140	300	460	680	990	1260
38						130	280	440	630	790	1140
40						130	220	350	510	770	1000
42							220	330	490	710	790
44							200	280	390	570	760
46							150	260	370	550	730
48							150	240	350	520	580
50							140	190	350	400	560